


W 640 - W700 FRAME & MULLION RE-INFORCEMENT

Thickness : 1.25 To 2.00


Tolerances : -0.5 mm



W 640 - W700 SASH RE-INFORCEMENT

Thickness : 1.25 To 2.00


Tolerances : -0.5 mm



W 640 - W700 DOOR SASH RE-INFORCEMENT

Thickness : 1.25 To 2.00


Tolerances : -0.5 mm



W700 FRAME WITH SILL RE-INFORCEMENT

Thickness : 1.25 To 2.00


Tolerances : -0.5 mm



W640-700 LAP JOINT RE-INFORCEMENT

Thickness : 1.25 To 2.00



Tolerances : -0.5 mm



W640-700 CORNER 135° RE-INFORCEMENT

Thickness : 1.25 To 2.00


Tolerances : -0.5 mm



W 260 FRAME RE-INFORCEMENT (SINGLE & DOUBLE RAIL)

Thickness : 1.25 To 2.00


Tolerances : -0.5 mm



W 260 SASH & W640 SUPER FRAME RE-INFORCEMENT

Thickness : 1.25 To 2.00


Tolerances : -0.5 mm



W 260 CORNICE (SINGLE RAIL) RE-INFORCEMENT

Thickness : 1.25 To 2.00

Tolerances : -0.5 mm



W640-700 CORNER 90° RE-INFORCEMENT

Thickness : 1.25 To 2.00

Tolerances : -0.5 mm

